

## SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

Page: 1

Compilation date: 18/01/2011

Revision date: 20/12/2019

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** LimeGrid Bound UV Resin - Part B

**CAS number:** 28182-81-2

**EINECS number:** 931-274-8

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Polyurethane Binder.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Limegate Solutions Ltd  
Unit 6, Murray Business Centre  
Murray Road  
Orpington  
Kent  
BR5 3RE  
United Kingdom  
**Tel:** +44 (0)1959 546208  
**Email:** info@limegatesolutions.co.uk

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)1959 546208  
(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335; -: EUH208

**Most important adverse effects:** Contains hexamethylene-di-isocyanate. May produce an allergic reaction. Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** EUH208: Contains hexamethylene-di-isocyanate. May produce an allergic reaction.  
H332: Harmful if inhaled.  
H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.

# SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

**Hazard pictograms:** GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P285: In case of inadequate ventilation wear respiratory protection.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

ALIPHATIC POLYISOCYANATE OLIGOMER - REACH registered number(s): 01-2119485796-17-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-060-2	28182-81-2	-	Acute Tox. 3: H331; Skin Sens. 1: H317; STOT SE 3: H335	>90%

HEXAMETHYLENE-DI-ISOCYANATE

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%
-----------	----------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

# SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

Page: 3

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

[cont...]

**SAFETY DATA SHEET**  
LimeGrid Bound UV Resin - Part B

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**HEXAMETHYLENE-DI-ISOCYANATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Colourless

**Odour:** Barely perceptible odour

**Evaporation rate:** Negligible

**Oxidising:** No data available.

**Solubility in water:** Insoluble, reacts with water

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Kinematic viscosity:** 1400

**Viscosity test method:** cps @ 25C

# SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

Page: 5

**Boiling point/range°C:** >35

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** 252

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

**Relative density:** 1.16

**pH:** Approx. 7

**VOC g/l:** No data available.

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### HEXAMETHYLENE-DI-ISOCYANATE

IVN	MUS	LD50	5600	µg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	µl/kg

**Relevant hazards for product:**

Hazard	Route	Basis
--------	-------	-------

[cont...]

# SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

Page: 6

Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Either return any unused product to the supplier, or Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08-04-10\* (20-01-27\*)

**Disposal of packaging:** Allow container residue to moisture cure to an inert polyurethane resin. Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

[cont...]

# SAFETY DATA SHEET

LimeGrid Bound UV Resin - Part B

Page: 7

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.